

NEW TPG4 Series Features

TSURUMI TPG4 SERIES GENERATORS are designed to withstand the severe conditions of construction jobsites or industrial applications, especially where extra durability and dependable, stable power are required. Ideal for supplying the power to Tsurumi's single-phase submersible pumps and all your electrical power tools such as drills, saws, lighting and heaters.

	TPG4-3000HDX	TPG4-4500HDX	TPG4-6000HDX	TPG4-7000HDX TPG4-7000HDXE
Max. / Rated Output (watts)	2600 / 2200	4500 / 3600	5500 / 4800	6800 / 6000
Max. / Rated Current (120V / 240V)	23.3 / 18.3	37.5/30, 18.7/15	45.8/40, 22.9/20	56.7/50, 28.3/25
Voltage (V) (60Hz)	120	120 / 240	120 / 240	120 / 240
AC Outlet Replacement	1-NEMA 5-20R Duplex (20A, 12A, W/GFCI)	2-NEMA 5-20A Duplex (20A, 12A, W/GFCI) 1-NEMA L5-30R (30A, 120V, Twist Lock) 1-NEMA L14-20R (30A, 120/240V, Twist Lock)		2-NEMA 5-20A Duplex (20A, 12A, W/GFCI) 1-NEMA L5-30R (30A, 120V, Twist Lock) 1-NEMA L14-20R (30A, 120/240V, Twist Lock)
Engine Model	GX160T2	GX240T2	GX340T2	GX390T2
Maximum HP	5.5 (3600RPM)	8.0 (3600RPM)	11.0 (3600RPM)	13.0 (3600RPM)
Displacement	163 (10inch ³)	242 (15inch ³)	337 (21inch ³)	389 (24inch ³)
Fuel Tank Capacity (gallon)	4.2	6.6	6.6	6.6
Running Time (Rated load)	12.1	12.5	8.5	7.6
Starting System	Recoil	Recoil	Recoil	Recoil (HDX), Electric (HDXE)
Noise Level (Rated Load)	64dB	68dB	72dB	78dB
Shipping Size (LxWxH) (inches)	24.4 x 19.5 x 20.5	27.6 x 23.4 x 22.6	27.6 x 23.4 x 22.6	27.6 x 23.4 x 22.6
Shipping Weight (lbs.)	110	161	183	192(HDX), 199 (HDXE)



NEW